

RightAngle.075 X .075 (Style 19) Connectors

Style 19 is a condensed footprint right angle connector designed for flex circuit applications where a jackscrew is required. It shares the same condensed footprint as Style 9 and serves as a drop-in replacement for the MR75 series industry standard. Spacing between rows is 0.075", and spacing between contacts in each row is 0.075" for 9 through 100 contact layouts.






KEY FEATURES & BENEFITS

- Condensed footprint right angle design.
- Optimized for flex circuit applications.
- Includes jackscrew for secure connection.
- Drop-in replacement for MR75 series industry standard.
- 0.075" row and contact spacing for 9–100 layouts.

Micro-D PCB Right Angle .075 X .075 (Style 19)

DIMENSIONAL



Size	A Max.	B Nom.	C Max.	E Max.	F Max.	G Max.	H Nom.
9	.785 (19.94)	.565 (14.35)	.400 (10.16)	.308 (7.82)	.410 (10.41)	.250 (6.35)	.138 (3.51)
15	.935 (23.75)	.715 (18.16)	.550 (13.97)	.308 (7.82)	.410 (10.41)	.250 (6.35)	.138 (3.51)
21	1.085 (27.56)	.865 (21.97)	.700 (17.78)	.308 (7.82)	.410 (10.41)	.250 (6.35)	.138 (3.51)
25	1.185 (30.10)	.965 (24.51)	.800 (20.32)	.308 (7.82)	.410 (10.41)	.250 (6.35)	.138 (3.51)
31	1.335 (33.91)	1.115 (28.32)	.950 (24.13)	.308 (7.82)	.410 (10.41)	.250 (6.35)	.138 (3.51)
37	1.485 (37.72)	1.265 (32.13)	1.100 (27.94)	.308 (7.82)	.410 (10.41)	.250 (6.35)	.138 (3.51)

Micro-D PCB Right Angle .075 X .075 (Style 19)

PERFORMANCE

Electrical Properties	
Contact Resistance	8 millihom max contact only + any solid lead resistance (depends on wire AWG) @ 2.5A
Current Rating	3A max.
Dielectric WithStanding Voltage	600 VAC at sea level, 150 VAC at 70,000 feet. 1mA leakage current max.
Insulation Resistance	500 VDC and 5000 Megohms min.

Mechanical Properties	
Engaging Force	6 oz max. (Signal contacts only, no data for Power or Coax contacts)
Separation Force	.5 oz. min. (Signal contacts only, no data for Power or Coax contacts)
Mating/Unmating Force	10 oz x # of contacts max. (Signal contacts only, no data for Power or Coax contacts)
Vibration	EIA-364-28 Condition IV, 1 microsecond max discontinuity
Shock	EIA-364-27 Condition E, 1 microsecond max discontinuity
Durability	500 matings, passes Mating Force, CR, Eng and Sep Forces
Salt Spray	EIA 364-26 Condition B-48 hours


Micro-D PCB Right Angle .075 X .075 (Style 19)

MATERIALS

Materials and Finishes	
Signal Pin Contacts	C17200 Beryllium Copper per ASTM B194
Signal Socket Contacts	C21000 Brass Alloy per ASTM B36
Contact Plating	.000050 Thk Gold Plating per ASTM B488
PC Tails	Copper Wire per A-A-59551 Type S
PC Tail Plating	.000320 min thk Tin plating per ASTM B545, or .000300 min thk Tin/Lead with minimum 3% lead plating per SAE-AMS-P-81728, or .000010 thk Gold plating per ASTM B488
Shell	6061-T6 Aluminum per SAE-AMS-QQ-A200/8 or Passivated 300 Series Stainless Steel
Shell Plating	Electroless Nickel per AMS 2404 or Cadmium Plated per SAE-AMS-QQ-P-416
Insulator Material	Polyphenylene Sulfide (PPS) Per MIL-M-24519 GST-40F
Hardware	Passivated Stainless Steel Per MIL-DTL-83513/05
Interfacial Seals	Fluorosilicone per MIL-R-25988 (Std Profile Receptacles only)

Micro-D PCB Right Angle .075 X .075 (Style 19)

HOW TO ORDER



*For 24 AWG, Pure Tin Plated, 0.109 Length Leads this section of the part number may be omitted