
Ulti-Mate Connectors

Ulti-Mate Nano PCB

Right Angle Dual Row SMT Plastic Shell Female Only Plastic Shell (Style 38) Connectors

Winchester Interconnect Micro offers Nano PCB Right Angle Dual Row SMT Plastic Shell Female Only (Style 38) Connectors, built for precision, durability, and high reliability in compact PCB designs. Featuring a Surface Mount .025 x .040 (Style 38) configuration with a 1-piece contact design and rectangular flat tail, these connectors ensure excellent solder results without lead deformation. Operating across a wide temperature range from −55°C to 125°C, with high-temperature versions available up to 200°C (add HT), they deliver consistent performance in demanding environments.




KEY FEATURES & BENEFITS

- Plastic Shell Construction – Lightweight yet durable, ideal for space-limited PCB layouts.
- Rectangular Flat Tail Design – Ensures consistent solder joints and prevents lead deformation.
- Wide Operating Range – Performs reliably from −55°C to 125°C; HT versions rated up to 200°C.
- Versatile Contact Options – Available with 9 to 65 contacts to meet varied design needs.
- High-Quality Materials – Signal pin and socket contacts made from C17410 Beryllium Copper for excellent conductivity.
- Durable Plating – Gold contact plating per ASTM B488; PC tail plating available in 60/40 Tin/Lead (SAE-AMS-P-81728) or Gold (ASTM B488).
- Ideal for High-Density PCB Applications – Provides precision connectivity and dependable performance in compact, mission-critical systems.

Winchester Interconnect

Nano PCB Right Angle SMT Extended Profile Female Only Plastic Shell (Style 38)


DIMENSIONAL




Size	A	B	C		D
			Receptacle	Plug	
9	.375 [9.52]	.270 [6.86]	.160 [4.06]	.163 [4.14]	.175 [4.44]
15	.450 [11.43]	.345 [8.76]	.235 [5.97]	.238 [6.04]	.250 [6.35]
21	.525 [13.33]	.420 [10.67]	.310 [7.87]	.313 [7.95]	.325 [8.25]
25	.575 [14.60]	.470 [11.94]	.360 [9.14]	.363 [9.22]	.375 [9.52]
31	.650 [16.51]	.545 [13.84]	.435 [11.05]	.438 [11.12]	.450 [11.43]
37	.725 [18.41]	.620 [15.75]	.510 [12.95]	.513 [13.03]	.525 [13.33]
51	.900 [22.86]	.795 [20.19]	.685 [17.40]	.688 [17.47]	.700 [17.78]
65	1.075 [27.30]	.970 [24.64]	.860 [21.84]	.863 [21.92]	.875 [22.22]


Nano PCB Right Angle SMT Extended Profile Female Only Plastic Shell (Style 38)

PCB







PAD DETAIL




SIZE 9 - VIEW A




SIZE 15 - VIEW A




SIZE 21 - VIEW A




SIZE 25 - VIEW A




SIZE 31 - VIEW A



SIZE 37 - VIEW A



SIZE 51 - VIEW A



SIZE 65 - VIEW A

Winchester Interconnect.

PERFORMANCE

Electrical Properties	
Contact Resistance	33 milliohm max contact only and 87 milliohms max with 6" wire @ 1A
Current Rating	1A max.
Dielectric WithStanding Voltage	250 VAC at sea level, 100 VAC at 70,000 feet. 1mA leakage current max.
Insulation Resistance	100 VDC and 5000 Megohms min.

Mechanical	
Engaging Force	5 oz max.
Separation Force	.4 oz min.
Mating/Unmating Force	7 oz x # of contacts max.
Vibration	EIA-364-28 Condition IV, 1 microsecond max discontinuity
Shock	EIA-364-27 Condition G, 1 microsecond max discontinuity
Durability	EIA-364-09, 200 matings, passes Mating Force, CR, Eng and Sep Forces

MATERIALS

Materials and Finishes	
Signal Pin Contacts	C17410 Beryllium Copper per ASTM B768
Signal Socket Contacts	C17410 Beryllium Copper per ASTM B768
Contact Plating	Gold Plating per ASTM B488
PC Tails	C17410 Beryllium Copper per ASTM B768
PC Tail Plating	60/40 Tin/Lead plating per SAE-AMS-P-81728, or Gold plating per ASTM B488
Shell	6061-T6 Aluminum per SAE-AMS-QQ-A200/8 or 300 Series Stainless Steel per ASTM A582
Shell Plating	Electroless Nickel per SAE-AMS2404, or Cadmium per SAE-AMS-QQ-P-416 or Black Anodize per MIL-A-8625 or Passivated per AMS2700
Insulator Material	LCP(Liquid Crystal Polymer) GLCP-30F or PPS per MIL-M-24519 GST-40F
Hardware	300 Series Stainless Steel per ASTM A 582/A582 or ASTM A 581/A581M, Passivated per SAE AMS-2700

Nano PCB Right Angle SMT Extended Profile Female Only Plastic Shell (Style 38)

HOW TO ORDER

Nano Circuit Series Engineering Number Definitions

CN M 6 L 25 - 2 P 07 1 - 0.140 - S01 - HT - 1 SPL

Nano Circuit Series

Shell Material
M = Metal Shell
P = Plastic Shell

Termination Style
4 = Flex Circuit
6 = Vertical PC tails
8 = Right Angle PC Tails
26 = Vertical SMT
28 = Right Angle SMT
36 = Low Profile Vertical SMT (Male Only)
38 = Extended Profile RA SMT (Female Only)

Insulator Material
L = LCP

Size (No. of Contacts)
09, 15, 21, 25, 31, 37, 51, 65, & 69

Insulator Type
1 = Single Row (Up to size 51)
2 = Dual Row

Contact Type
P = Pin, Integral Flat Tail
S = Socket, Integral Flat Tail

Mating Hardware
0 = No Hardware
01 = Phillips Head Jackscrews
02 = Hex Head Jackscrews
03 = Thumb Jackscrew
05 = Slotted Head Jackscrews
06 = Floating Phillips Head Jackscrews (Female Only)
07 = Threaded Hole
08 = Floating (Retractable) Hex Head Jackscrews (Female Only)
09 = Floating (Retractable) Slotted Head Jackscrews (Female Only)

Lead Plating
1 = Tin/Lead (minimum 3% Lead) plated (Not RoHS Compliant) (Not Available with high temp (HT) connectors)
2 = Gold Plated (RoHS Compliant)

Board Thickness (Style 4 Only)
Blank = .010
Other Panel Thicknesses 0.030 & 0.054
(Consult Factory for Additional Thicknesses)

Lead Length (Style 6 and 8 Only)
Blank = 0.109
Other Lengths = 0.140 & 0.172
(Consult Factory for Additional Lengths)

Shell Plating or Material (Omit for plastic shell or cadmium plating)
Blank = Cadmium
S01 = Electroless Nickel
S02 = Chem Film
S03 = Black Anodized
S04 = Gold
S05 = Titanium
S06 = Olive-Drab Cadmium
S07 = Black Nickel
S08 = Nickel-PTFE
S09 = Stainless Steel, Passivated
S10 = Zinc Nickel

Temperature Rating (Omit for standard Temp, 125°C)
Blank = 125°C
HT = 200°C
LO = 4 Kelvin

PCB Mounting Options (Style 8, 28, & 38 Only)
Blank = Threaded Mounting Holes
1 = Alignment Posts with Threaded Mounting Holes
2 = Clearance Mounting Holes
3 = Alignment Posts with Clearance Mounting Holes
4 = Solder Posts (Style 6, 8, 26, 28, 36, & 38)

Special designator - SPL is to be added to the end of the part number if the connector cannot be fully defined by the rest of the engineering number

Winchester Interconnect