

10

9

8

7

6

5


4

3



2

SD-8361X9048

PART REV	DWG ISSUE	DATE	ECN NO.	APPVD BY	REL BY



5 2-56 JACKSCREWS
2 PLACES



PART NUMBER	SIZE	A MAX	B	C MAX
836119048	9	.785 [19.94]	.565 [14.35]	.400 [10.16]
836129048	15	.935 [23.75]	.715 [18.16]	.550 [13.97]
836139011	21	1.085 [27.56]	.865 [21.97]	.700 [17.78]
836149039	25	1.185 [30.10]	.965 [24.51]	.800 [20.32]
836159018	31	1.335 [33.91]	1.115 [28.32]	.950 [24.13]
836169024	37	1.485 [37.27]	1.265 [32.13]	1.100 [27.94]

- 5 CONSULT FACTORY FOR AVAILABLE OPTIONS
4. PERFORMANCE: MEETS OR EXCEEDS THE REQUIREMENTS OF MIL-DTL-83513
3. SEE SHEET 2 FOR RECOMMENDED PCB LAYOUTS
- 2 MATERIALS:
SHELL: 6061-T6 ALUMINUM PER AMS-QQ-A200/8, NICKEL
PLATED PER AMS 2404
INSULATOR AND BACKSHELL: PPS PER MIL-M-24519 GST-40F, COLOR: BLACK
PIN CONTACTS: C17200 BERYLLIUM COPPER PER ASTM B194,
GOLD PLATED PER ASTM B488
24 AWG LEADS: TIN PLATED COPPER ALLOY PER A-A-59551 TYPE S
JACKPOSTS: PASSIVATED STAINLESS STEEL IAW MIL-DTL-83513/5
1. MARKING: "UMI", DATE CODE, AND UMI PART NUMBER
- NOTES: UNLESS OTHERWISE SPECIFIED

QUALITY SYMBOLS	UNLESS SPECIFIED: ALL DIMENSIONS IN INCHES/MM	SCALE 4:1	DWG SIZE B	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
MAJOR CRITICAL SPC	GENERAL TOLERANCES: 3 PLACE ±.002/-.051 2 PLACE ±.005/-.13 ANGULAR ±2°	DRAWN BY & DATE DW 2-9-12	CHECKED BY & DATE	APPROVED BY & DATE	TITLE: CIRCUIT CONNECTOR, PLUG, STYLE 19 (.075 X .075), SIZES 9 THRU 37, CMI 9RXXP02-S01
	Ulti-Mate CAGE CODE 58967	CAD FILENAME SD-8361X9048-1.DGN	PART NO. SEE CHART	DRAWING NO. SD-8361X9048	SHEET NO. 1 OF 2
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ULTI-MATE INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.			REV

